Tora

SRX 5800/6800

SN 6800 V

NEW TORA SERIES

The **TORA** series was conceived as a range of medium-power tractors for professionals characterized by upgraded hydraulics, mechanical equipment and operator comfort. The underlying principle is that fuel consumption and running costs must be taken into account in all agricultural applications, and that the power delivered by the tractor should always be commensurate with the task to be performed, thereby ensuring maximum efficiency with minimum wastage of time and effort.

ANTONIOCARRARO.COM

ANTONIO CARRARO
TRACTOR PEOPLE

N#1 SPECIAL TRACTORS

TECHNICAL DATA:
SRX 5800/6800 - SN 6800 V

Frame	ACTIO™ integral oscillating frame • RGS™ reversible drive system **(SRX)** • Unidirectional **(SN)** • Articulated frame • Four equal-size wheels • Rear final drives	
Engine type	Diesel with common rail direct injection, with turbo and intercooler on the 6800 Emissions Standard: **Stage 5** No. of cylinders: 4 - 8 Valves Rated rpm: 2600 Tank capacity (litres): 40	Power kW/CV (97/68/CE): 37.9/ 52 **(5800)** 48.5/ 66 **(6800)** Max torque (Nm@rpm): 170 Nm/1690 **(5800)** 210 Nm/1690 **(6800)**
Transmission	S90: 32 speed synchronised gearbox: 16 FWD + 16 REV with synchronised shuttle. Electrohydraulic control of rear differential lock; mechanical control of front differential lock. Permanent all-wheel drive	
Power take-off	Rear, independent 540/540E rpm with progressive electro-hydraulic engagement; synchronised groundspeed	
Shaft	6 spline 1 3/8" shaft with easy coupling	
Hydraulic system	Load sensing hydraulic system. Rear auxiliary hydraulic system with 1 double-acting remote valve with float and 1 oil return (3 rear hydraulic couplers). Pump capacity 37 l/min	
Rear power lift	Hydraulic lift with 3-point linkage Lifting capacity at the hitch balls (kg): 2190 Oscillating lift arms and lateral stabilizer bars, Cat. 1-2; Category "C" height-adjustable rear tow hook	
Steering	Hydraulic 2 piston	
Brakes	Rear service brakes: oil-immersed dual discs with hydraulic control; Combination parking brake: band brake on transmission and integrated mechanical Superbrake system acting on blocks.	
Platform	Suspended on Silent Blocks	
Weight	SRX roll-bar 1775÷1965 kg SN roll-bar 1175÷1965 kg	SRX cab. 1925÷2115 kg SN cab. 1925÷2115 kg

COD. 4 7318 565 - 07/2021

The descriptions and images in this brochure are for illustrative purposes only and therefore are not binding and are subject to modification without notice.